°FORM PTO-1390 (REV 11-2000) U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. § 371

ATTORNEY'S DOCKET NUMBER: 449122011900

U.S. APPLICATION NO. (If known, see 37 CFR 1.5): 10/018845 Not yet assigned

INTERNATIONAL APPLICATION NO.	INTERNATIONAL FILING DATE	PRIORITY DATE CLAIMED
PCT/DE00/01981	June 20, 2000	June 22,1999

TITLE OF INVENTION

MAGNETIC LINEAR DRIVE

APPLICANT(S) FOR DO/EO/US

Andreas ARNDT et al.

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☐ This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include items (5), (6), (9) and (21) indicated below.
4. ☒ The US has been elected by the expiration of 19 months from the priority date (PCT Article 31).
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
   a. ☒ is attached hereto (required only if not communicated by the International Bureau).
   b. ☒ has been communicated by the International Bureau.
   c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ An English language translation of the International Application under PCT Article 19 (35 U.S.C. 371(c)(2)).
   a. ☒ is attached hereto.
   b. ☒ has been previously submitted under 35 U.S.C. 154(d)(4).
7. ☐ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)).
   a. ☐ are attached hereto (required only if not communicated by the International Bureau).
   b. ☐ have been communicated by the International Bureau.
   c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
   d. ☐ have not been made and will not be made.
8. ☐ An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ An English language translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11. to 16. below concern document(s) or information included:

11. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☒ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☐ A FIRST preliminary amendment.
14. ☐ A SECOND or SUBSEQUENT preliminary amendment.
15. ☐ A substitute specification.
16. ☐ A change of power of attorney and/or address letter.
17. ☐ A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825.
18. ☐ A second copy of the published international application under 35 U.S.C. 154(d)(4).
19. ☐ A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4).
20. ☒ Other items or information: 1) Application Data Sheet; 2)Int'l Search Report; 3) IPER; 4) Return receipt postcard.

CERTIFICATE OF HAND DELIVERY

I hereby certify that this correspondence is being hand filed with the United States Patent and Trademark Office in Washington, D.C. on December 21, 2001.

Melissa Garton

Melissa Garton

dc-292929

U.S. APPLICATION NO. (if known, see 37 CFR 1.5)	INTERNATIONAL APPLICATION NO.	ATTORNEY DOCKET NO.
Not yet assigned 10/018845	PCT/DE00/01981	449122011900

21. ☒ The following fees are submitted:

BASIC NATIONAL FEE (37 CFR 1.492(a)(1)-(5)):

Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO.....$1,000.00

International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO.....$860.00

International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO.....$710.00

International preliminary examination fee (37 CFR 1.482) paid to USPTO but all claims did not satisfy provision of PCT Article 33(1)-(4) $690.00

International preliminary examination fee (37 CFR 1.482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4) $100.00

	CALCULATIONS PTO USE ONLY	
ENTER APPROPRIATE BASIC FEE AMOUNT =	$860.00	
Surcharge of **$130.00** for furnishing the oath or declaration later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492(e)).	$0	

CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE		
Total claims	- 20 =		x $18.00	$0	
Independent claims	- 3 =		x $80.00	$0	
MULTIPLE DEPENDENT CLAIM(S) (if applicable)			+ $270.00	$0	
			TOTAL OF ABOVE CALCULATIONS =	$860.00	
☐ Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above are reduced by ½.				$0	
			SUBTOTAL =	$0	
Processing fee of **$130.00** for furnishing the English translation later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492(f)). +				$0	
			TOTAL NATIONAL FEE =	$0	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). **$40.00 per property** +				$40.00	
			TOTAL FEES ENCLOSED =	$900.00	
			Amount to be refunded:		**$**
			charged:		**$**

a. ☒ Please charge my **Deposit Account No. 03-1952** (referencing Docket No. 44912-20119.00) in the amount of $900.00 to cover the above fees. A duplicate copy of this sheet is enclosed.

b. ☒ The Commissioner is hereby authorized to charge any additional fees that may be required, or credit any overpayment to **Deposit Account No. 03-1952** (referencing Docket No. 44912-20119.00).

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

Kevin R. Spivak
Morrison & Foerster LLP
2000 Pennsylvania Avenue, N.W.
Washington, D.C. 20006-1888

SIGNATURE

Kevin R. Spivak
Registration No. 43,148

December 21, 2001

Description

Magnetic linear drive

The invention relates to a magnetic linear drive, in particular for an electrical switch, having a coil through which a current can be passed and in whose interior the current can produce a magnetic flux in an axial direction, having an armature which can move only at right angles to the axial direction and which has a magnetically active part whose movement path passes through an airgap within a core which passes through the coil, or passes one end face of the core, with the magnetically active part being demagnetized or magnetized in such a manner that the magnetic flux runs parallel to the axial direction, or parallel to it but in the opposite direction, within the magnetically active part.

A magnetic linear drive for accelerating a projectile is known from US Patent Specification 4,817,494.

A magnetic linear drive is likewise known from US Patent Specification 5,719,451, where it is used, for example, in pumps for liquids. The linear drives described there have the common feature that a magnet coil accelerates an armature in the axial direction of the coil.

Such a magnetic linear drive is also known, for example, from GB 10 68 610. The drive described there is a drive for a valve, in which a channel for liquid is shut off or opened by means of the movement of an armature.

There, the armature has a permanent magnet whose magnetic flux in its interior is directed in the movement direction of the armature, and at right angles to the axial direction.

At each of its limit positions, the armature runs into mechanical stops such that one pole of the permanent magnet always comes into contact with the stop, and such that the magnetic effect of the permanent magnet holds it against the stop.

If a current is passed through the coil, then the magnetic effect of the current first of all has to cross the holding force of the permanent magnet against the stop. This results in a delay to the armature acceleration. Furthermore, during its movement toward a limit position, the armature is drawn toward the stop only immediately before reaching it, since the airgap located between the pole of the permanent magnet and the stop surface becomes sufficiently reduced in size only toward the end of the movement.

In contrast, the present invention is based on the object of providing a magnetic linear drive of the type mentioned initially, which achieves undelayed acceleration of the armature, with little design complexity and with little control complexity.

According to the invention, the object is achieved in that the magnetically active part can be positioned permanently in two limit positions, and can be moved from a first limit position to a second limit position by the influence of a current.

When a current is passed through the coil, a magnetic flux is produced in the axial direction in its interior, runs within the core and emerges from the core in the region of the airgap. A magnetically active part of an armature which, for example, is ferromagnetically demagnetized or magnetized, in particular being permanent-magnetized in a direction opposite to but parallel to the direction of magnetic flux of the coil, is accelerated toward the coil interior. A magnet, whose internal magnetic flux is aligned parallel to the flux of the coil, is repelled out of the interior of the coil. This effect is used to drive the armature.

Especially if the magnetically active part is magnetized ferromagnetically or as a permanent magnet parallel to but in the opposite direction to the axial direction, the magnetic linear drive can advantageously be used as a switch drive for an electrical switch, for example a high-voltage circuit breaker or a vacuum interrupter.

If the armature is located at a limit position of its movement path such that, when the coil current is switched on, a small proportion of the magnetic flux of the coil passes through the magnetically active part, then this leads to the armature being accelerated toward the coil center, until the maximum proportion of the magnetic flux of the coil passes through the magnetically active part. During the movement of the armature, the current flow through the coil is interrupted by means of a control device, so that the armature moves further out from the coil by virtue of its kinetic energy and the kinetic energy of the driven masses, without any possibility of the magnetic flux of the coil being able to brake the armature

by any influence on the magnetically active part.

This ensures optimum acceleration of the armature at the start of the movement.

A desired armature acceleration profile can be achieved, for example, by designing the airgap to have different widths along the movement path between the core and the movement path of the magnetically active part. The narrower the airgap in a specific region along the movement path, the greater is the force that acts on the armature in this region.

By way of example, a drive rod of an electrical switch is connected to the armature, and itself drives a switching contact of an interrupter unit.

Mechanical stops can be provided in the region of the switching rod, or in the region of the linear drive itself.

One advantageous refinement of the invention provides that the magnetically active part is magnetized, and that, in at least one limit position of the magnetically active part, this part is arranged at least partially in the region of a yoke body which is arranged outside the coil, such that the magnetic flux emerging from the magnetically active part, or entering it, passes at least partially directly through a boundary surface of the yoke body facing the magnetically active part.

The boundary surface is advantageously aligned essentially at right angles to the axial direction.

In the situation where the magnetically active part is magnetized, for example as an electromagnet, or is permanently magnetized, the magnetic flux of the magnetically active part has the tendency to reduce the size of the airgap from a yoke body, which is arranged adjacent, as much as possible.

At least one yoke body is arranged in the end region of the movement path of the armature, which the magnetic flux of the magnetically active part can enter, at least over a portion of the length of the magnetically active part.

The armature is thus subject to a force which attempts to produce as much overlap as possible between the magnetically active part and the yoke body, such that, as far as possible, the entire magnetic flux of the magnetically active part can enter the yoke body through a boundary surface which is arranged as far as possible at right angles to the axial direction. The force acting in the direction of the movement path of the armature is essentially independent of the extent to which the magnetically active part and yoke body overlap.

This results in a holding force which is essentially independent of the position of the armature in the end region of the movement, and holds the armature in one of its limit positions.

Such an arrangement can advantageously be provided for both limit positions of the magnetically active part or armature.

A further advantageous refinement of the invention provides that a second coil is located opposite the coil with respect to the movement path of the

magnetically active part and a current can be passed through it in the same direction sense as the first coil.

Two coils that are combined in the illustrated manner make it possible to produce a correspondingly greater magnetic flux, which leads to greater potential acceleration of the armature.

It can furthermore be provided for the first coil and the second coil to be offset with respect to one another in the movement direction of the armature.

Such an offset of the coils in the movement direction of the armature with respect to one another makes it possible to achieve a specific acceleration profile along the movement path.

It is also possible to provide for each of the coils to be used for in each case one of the movement directions of the armature.

It may also be advantageous to provide two yoke bodies which are opposite one another with respect to the movement path of the magnetically active part and form airgaps between them, through which at least part of the movement path of the magnetically active part passes.

A further yoke body, which is opposite the first yoke body with respect to the movement path of the magnetically active part, makes it possible to close the magnetic circuit both for the flux through the coil and for the flux of the magnetically active part in each of the limit positions, thus in each case resulting in a large amount of force being produced both for acceleration and for the holding force in the limit positions.

A further advantageous refinement of the invention provides that a number of energy-storage capacitors, which can be charged and can be connected jointly or alternatively to a coil on a case-by-case basis, are provided in the control device.

The various energy-storage capacitors can be used for different switching situations (for example different load situations in a circuit breaker that is to be driven), or can be used differently for connection and disconnection.

The invention also relates to a method for operating a magnetic linear drive, which provides that the coil in each case has a current passed through it in the same direction in order to drive the armature in different directions.

Irrespective of which limit position the armature or the magnetically active part is located in, it is accelerated toward the coil interior when a magnetic flux is produced in the interior of the coil. If the current through the coil is interrupted at the right time, then the armature moves to the respective other limit position. This makes it considerably easier to drive the coil.

The method according to the invention can advantageously be refined such that the passing of a current is ended before the magnetically active part has reached its limit position.

A further advantageous refinement provides that the current flow through the coil is interrupted as soon as the supply voltage changes its mathematical sign owing to an electrical oscillation process.

Since the coil represents an electrical inductance and a resistance, and is normally supplied by means of a capacitance, this results in an electrical resonant circuit in the drive for the linear drive. This leads to the creation of an electrical oscillation, so that the supply voltage applied to the coil reverses its mathematical sign at some time.

This would result in reversal of the magnetic flux, which would mean a reversal of the magnetic force acting on the magnetically active part, which is undesirable. The supply voltage is thus advantageously monitored, and the current flow through the coil is interrupted as soon as the supply voltage reverses its mathematical sign.

It is also advantageously possible to provide for the current flow to be diverted to an energy-storage capacitor as soon as the supply voltage reverses its mathematical sign owing to an electrical oscillation process.

The invention is illustrated with respect to an exemplary embodiment in a drawing, and will then be described in the following text.

In the drawing:

Figure 1 shows the magnetic linear drive schematically, in the form of a cross section,

Figure 2 shows a drive circuit for the coil for the linear drive, and

Figure 3 shows the power supply for the linear drive, schematically.

Figure 1 shows a magnetic linear drive having an armature 1 which comprises a rod 2 made of glass-fiber-reinforced plastic and a magnetically active part 3 made of permanently magnetic material, and to which, at one end, a switching rod 4 is coupled, which is illustrated only schematically and is connected to a drivable switching contact 5 of the interrupter unit of a high-voltage circuit breaker. The linear drive produces movements in the direction of the double arrow 6.

The armature 1 moves in the airgap 7 between a first yoke body 8 and a second yoke body 9, which are opposite one another, in a mirror-image symmetrical arrangement, with respect to the movement path of the armature 1.

Each of the yoke bodes has an annular recess, into each of which a coil 10, 11 is fitted. The coils 10, 11 are each provided with electrical connections and a current can be passed through them by means of a control device.

When a current is passed through at least one of the coils 10, 11, then, for example, the current direction is such that the current runs into the plane of the drawing in the upper part of the coil 10, and the current emerges from the plane of the drawing in the lower part of the coil, as is indicated by the dot 12.

This results in a magnetic flux being produced in the axial direction 34, which is represented by the arrows 13 and passes through a first core 14 of the first yoke body 8 within the coil 10, and through a second core 15 of the second yoke body 9 within the coil 11.

In the illustrated armature limit position, in which said armature is in contact with a mechanical stop in a manner that is not shown, a portion 16 of the magnetic flux 13 of the coils 10, 11 passes through an edge region of the magnetically active part 3 of the armature at this stage.

The rest of the magnetic flux 13 of the coils 10, 11 have to cross the broad airgap between the coils 14, 15, which is not bridged by the glass-fiber plastic body of the armature 1.

The magnetic flux accordingly has the tendency to accelerate the magnetically active part 3 downward in the illustration, so that the magnetic flux 13 of the coils 10, 11 passes through the magnetically active part 3 over as much of its length as possible and runs parallel to, but in the opposite direction to, the magnetic flux 17 produced in the interior of the magnetically active part 3.

When the magnetically active part 3 arrives approximately in the center of the coils 10, 11, the current flow through the coils 10, 11 is interrupted, in order to prevent the magnetic part from being braked when it emerges from the flux 13 of the coils 10, 11.

Owing to its kinetic energy, the armature continues to move until the magnetically active part 3 reaches a second limit position 36, which is represented by dashed lines.

In the movement region before reaching the limit position, the magnetic flux 17 within the magnetically active part 3 tries to enter one of the

yoke bodies 8, 9, and emerge from it again, via an airgap which is as narrow as possible.

The holding forces acting on the armature in its limit positions will be described with reference to the upper limit position, illustrated in figure 1.

When the current flow through the coils 10, 11 is interrupted, the magnetic flux 13 decays.

A portion of the magnetic flux 17 in the interior of the magnetically active part 3 can enter the yoke body 8 directly through the boundary surface 35, with the flux path being closed via the second yoke body 9 with the interposition of the unavoidable airgaps, so that the magnetic flux can emerge from there once again into the magnetically active part 3.

The portions 18 of the magnetic flux in the magnetically active part 3, which are at the same level as a coil winding 10, 11, have to cross a broad airgap in order to enter a yoke body 8. The illustrated constellation thus tries to move the magnetically active part 3 further upward, in order to achieve as great an overlap as possible between the length of the magnetically active part 3 and the portion of the yoke body 8 above the coil 10.

The magnetic force acting on the armature 1 is in this case largely independent of the extent to which the magnetically active part 3 already overlaps the portion of the yoke body 8 above the coil 10. The holding force on the armature in the limit position is thus largely independent of mechanical tolerances.

A corresponding situation applies to the other limit position of the armature, illustrated by dashed lines.

It can also be seen from figure 1 that both yoke bodies 8, 9 are profiled along the movement path of the magnetically active part in the region of the cores 14, 15, such that the airgap between the armature 3 and the yoke bodies 8, 9 becomes broader in the upward direction. This means that the force acting on the magnetically active part 3 decreases during its upward movements. In this way, a high acceleration can be achieved at the start of the movement during disconnection of the interrupter unit, with the acceleration becoming weaker toward the end of the movement. It is also feasible, for example, for the second coil 11 to be offset downward along the movement path of the armature 1 with respect to the first coil 10, so that, during a disconnection process, that is to say a movement of the armature 1 in the upward direction, the second coil 11 would carry the main load of the acceleration initially, and the first coil 10 would carry it later.

This also allows specific profiling of the acceleration to be achieved.

Figure 2 shows a drive circuit having an energy-storage capacitor 19 which can be connected via a first IGBT (insulated gate bipolar transistor) 20 and a second IGBT 21 to the coil 22 within the magnetic linear drive. 23 denotes the resistance of the coil 22, and its supply leads, symbolically.

When the IGBTs 20, 21 are switched on, a current flows through the coil 22 in the direction of the arrow annotated

24. This current flows through the first IGBT 20, and further along the arrows 25, 26, 27.

As the capacitor 19 discharges, the voltage across the coil 22 falls, where a back e.m.f. is induced, which tries to maintain the current density of the current 24. The back e.m.f. across the coil 22 opposes the supply voltage, so that this results in a voltage zero crossing. The IGBTs 21, 22 are switched off at this time, that is to say they block the current.

The current induced by the voltage within the coil 22 flows via the diodes 28, 29 in the direction of the arrow 30 back to the capacitor 19, partially recharging it. Energy is thus saved during operation of the linear drive and this is particularly important when a high-voltage switch that is driven by this drive needs to be operated in a standby mode by means of batteries.

Figure 3 shows, schematically, a linear drive being supplied with power via three different drive units 31, 32, 33, each of which has its own energy-storage capacitor, in which case the energy-storage capacitors may have different capacitances. In consequence, a different amount of energy, in the form of electrical field energy stored in the energy-storage capacitors, is in each case made available for different switching situations.

The various drives 31, 32, 33 can also be used for rapidly successive off-on-off switching operations.

Patent Claims

1. A magnetic linear drive, in particular for an electrical switch, having a coil (10, 11) through which a current can be passed and in whose interior the current can produce a magnetic flux (13) in an axial direction (34), having an armature (1) which can move only at right angles to the axial direction (34) and which has a magnetically active part (3) whose movement path passes through an airgap (7) within a core (14, 15) which passes through the coil (10, 11), or passes one end face of the core (14, 15), with the magnetically active part (3) being demagnetized or magnetized in such a manner that the magnetic flux (17) runs parallel to the axial direction (34), or parallel to it but in the opposite direction, within the magnetically active part (3),
characterized in that
the magnetically active part can be positioned permanently in two limit positions, and can be moved from a first limit position to a second limit position by the influence of a current.

2. The magnetic linear drive as claimed in claim 1,
characterized in that
the magnetically active part (3) is magnetized, and in that, in at least one limit position of the magnetically active part (3), this part (3) is arranged at least partially in the region of a yoke body (8) which is arranged outside the coil, such that the magnetic flux (17) emerging from the magnetically active part (3), or entering it, passes at least partially directly through a boundary surface (35) of the yoke body facing the magnetically active part.

3. The magnetic linear drive as claimed in one of claims 1 or 2,
characterized in that
a second coil (11) is located opposite the coil (10) with respect to the movement path of the magnetically active part (3) and, together with the first coil (10), a current can be passed through it in the same direction sense as the first coil (10).

4. The magnetic linear drive as claimed in claim 1, 2 or 3,
characterized in that
the first coil (10) and the second coil (11) are offset with respect to one another in the movement direction of the armature (1).

5. The magnetic linear drive as claimed in one of claims 1 to 4,
characterized in that
two yoke bodies (8, 9) are provided, which are opposite one another with respect to the movement path of the magnetically active part (3) and form airgaps (7) between them, through which at least part of the movement path of the magnetically active part (3) passes.

6. The magnetic linear drive as claimed in one of claims 1 to 5 having a control device,
characterized in that
a number of energy-storage capacitors (19), which can be charged and can be connected jointly or alternatively to a coil on a case-by-case basis, are provided in the control device (31, 32, 33).

7. A method for operating a magnetic linear drive as claimed in claim 1,
characterized in that

the coil (10, 11) in each case has a current passed through it in the same direction

in order to drive the armature (1) in different directions.

8. The method as claimed in claim 7, characterized in that the passing of a current is ended before the magnetically active part (3) has reached its limit position.

9. The method as claimed in claim 8, characterized in that the current flow through the coil (10, 11) is interrupted as soon as the supply voltage changes its mathematical sign owing to an electrical oscillation process.

10. The method as claimed in claim 8, characterized in that the current flow is diverted to an energy-storage capacitor (19) as soon as the supply voltage changes its mathematical sign owing to an electrical oscillation process.

11. A method for operating a magnetic linear drive as claimed in claim 1, characterized in that first of all, a current is produced in the coil (10, 11), whose resultant magnetic flux in the coil (10, 11) is parallel to, but in the opposite direction to, any magnetization of the magnetically active part (3), provided this is magnetized, and in that, once the magnetically active part (3) has reached the location of the greatest magnetic field strength of the coil (10, 11) on its movement path, the current direction through the coil (10, 11) is reversed.

Declaration and Power of Attorney For Patent Application
Erklärung Für Patentanmeldungen Mit Vollmacht
German Language Declaration

Als nachstehend benannter Erfinder erkläre ich hiermit an Eides Statt:

dass mein Wohnsitz, meine Postanschrift, und meine Staatsangehörigkeit den im Nachstehenden nach meinem Namen aufgeführten Angaben entsprechen,

dass ich, nach bestem Wissen der ursprüngliche, erste und alleinige Erfinder (falls nachstehend nur ein Name angegeben ist) oder ein ursprünglicher, erster und Miterfinder (falls nachstehend mehrere Namen aufgeführt sind) des Gegenstandes bin, für den dieser Antrag gestellt wird und für den ein Patent beantragt wird für die Erfindung mit dem Titel:

Magnetischer Linearantrieb

deren Beschreibung

(zutreffendes ankreuzen)
☐ hier beigefügt ist.
☒ am 20.06.2000 als
PCT internationale Anmeldung
PCT Anmeldungsnummer PCT/DE00/01981
eingereicht wurde und am _____
abgeändert wurde (falls tatsächlich abgeändert).

Ich bestätige hiermit, dass ich den Inhalt der obigen Patentanmeldung einschliesslich der Ansprüche durchgesehen und verstanden habe, die eventuell durch einen Zusatzantrag wie oben erwähnt abgeändert wurde.

Ich erkenne meine Pflicht zur Offenbarung irgendwelcher Informationen, die für die Prüfung der vorliegenden Anmeldung in Einklang mit Absatz 37, Bundesgesetzbuch, Paragraph 1.56(a) von Wichtigkeit sind, an.

Ich beanspruche hiermit ausländische Prioritätsvorteile gemäss Abschnitt 35 der Zivilprozessordnung der Vereinigten Staaten, Paragraph 119 aller unten angegebenen Auslandsanmeldungen für ein Patent oder eine Erfindersurkunde, und habe auch alle Auslandsanmeldungen für ein Patent oder eine Erfindersurkunde nachstehend gekennzeichnet, die ein Anmeldedatum haben, das vor dem Anmeldedatum der Anmeldung liegt, für die Priorität beansprucht wird.

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

MAGNETIC LINEAR DRIVE

the specification of which

(check one)
☐ is attached hereto.
☒ was filed on 20.06.2000 as
PCT international application
PCT Application No. PCT/DE00/01981
and was amended on _____
(if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Form PTO-FB-240 (8-83)
Patent and Trademark Office-U.S. DEPARTMENT OF COMMERCE

German Language Declaration

Prior foreign appplications Priorität beansprucht			Priority Claimed	
19929572.7 (Number) (Nummer)	DE (Country) (Land)	1999.06.22 (Day Month Year Filed) (Tag Monat Jahr eingereicht)	☒ Yes Ja	☐ No Nein
(Number) (Nummer)	(Country) (Land)	(Day Month Year Filed) (Tag Monat Jahr eingereicht)	☐ Yes Ja	☐ No Nein
(Number) (Nummer)	(Country) (Land)	(Day Month Year Filed) (Tag Monat Jahr eingereicht)	☐ Yes Ja	☐ No Nein

Ich beanspruche hiermit gemäss Absatz 35 der Zivilprozessordnung der Vereinigten Staaten, Paragraph 120, den Vorzug aller unten aufgeführten Anmeldungen und falls der Gegenstand aus jedem Anspruch dieser Anmeldung nicht in einer früheren amerikanischen Patentanmeldung laut dem ersten Paragraphen des Absatzes 35 der Zivilprozeßordnung der Vereinigten Staaten, Paragraph 122 offenbart ist, erkenne ich gemäss Absatz 37, Bundesgesetzbuch, Paragraph 1.56(a) meine Pflicht zur Offenbarung von Informationen an, die zwischen dem Anmeldedatum der früheren Anmeldung und dem nationalen oder PCT internationalen Anmeldedatum dieser Anmeldung bekannt geworden sind.

I hereby claim the benefit under Title 35. United States Code. §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §122, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occured between the filing date of the prior application and the national or PCT international filing date of this application.

(Application Serial No.) (Anmeldeseriennummer)	(Filing Date D, M, Y) (Anmeldedatum T, M, J)	pending (Status) (patentiert, anhängig, aufgegeben)	(Status) (patented, pending, abandoned)
(Application Serial No.) (Anmeldeseriennummer)	(Filing Date D,M,Y) (Anmeldedatum T, M; J)	(Status) (patentiert, anhängig, aufgeben)	(Status) (patented, pending, abandoned)

Ich erkläre hiermit, dass alle von mir in der vorliegenden Erklärung gemachten Angaben nach meinem besten Wissen und Gewissen der vollen Wahrheit entsprechen, und dass ich diese eidesstattliche Erklärung in Kenntnis dessen abgebe, dass wissentlich und vorsätzlich falsche Angaben gemäss Paragraph 1001, Absatz 18 der Zivilprozessordnung der Vereinigten Staaten von Amerika mit Geldstrafe belegt und/oder Gefängnis bestraft werden koennen, und dass derartig wissentlich und vorsätzlich falsche Angaben die Gültigkeit der vorliegenden Patentanmeldung oder eines darauf erteilten Patentes gefährden können.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

German Language Declaration

VERTRETUNGSVOLLMACHT: Als benannter Erfinder beauftrage ich hiermit den nachstehend benannten Patentanwalt (oder die nachstehend benannten Patentanwälte) und/oder Patent-Agenten mit der Verfolgung der vorliegenden Patentanmeldung sowie mit der Abwicklung aller damit verbundenen Geschäfte vor dem Patent- und Warenzeichenamt: *(Name und Registrationsnummer anführen)*

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. *(list name and registration number)*

And I hereby appoint

Customer No. 25227

Telefongespräche bitte richten an:
(Name und Telefonnummer)

Direct Telephone Calls to: *(name and telephone number)*

Ext. _____

Postanschrift:

Send Correspondence to:

Morrison and Foerster LLP
2000 Pennsylvania Ave., NW 20006-1888 Washington, DC
Telephone: (001) 202 887 1500 and Facsimile (001) 202 887 0763
or
Customer No. 25227

Voller Name des einzigen oder ursprünglichen Erfinders:	Full name of sole or first inventor:
Andreas Arndt	Andreas Arndt
Unterschrift des Erfinders Datum	Inventor's signature Date
Andreas Arndt 24.09.01	Andreas Arndt 24.09.01
Wohnsitz	Residence
Algermissen, Deutschland	Algermissen, Germany
Staatsangehörigkeit	Citizenship
Deutsch	German DEX
Postanschrift	Post Office Addess
Lindenallee 12	Lindenallee 12
31191 Algermissen Deutschland	31191 Algermissen Germany
Voller Name des zweiten Miterfinders (falls zutreffend):	Full name of second joint inventor, if any:
Wolf Rüdiger Canders	Wolf Rüdiger Canders
Unterschrift des Erfinders Datum	Second Inventor's signature Date
Wohnsitz	Residence
Osterode/Harz, Deutschland	Osterode/Harz, Germany
Staatsangehörigkeit	Citizenship
Deutsch	German
Postanschrift	Post Office Address
Fuchshaller Weg 38	Fuchshaller Weg 38
37520 Osterode/Harz Deutschland	37520 Osterode/Harz Germany

(Bitte entsprechende Informationen und Unterschriften im Falle von dritten und weiteren Miterfindern angeben).

(Supply similar information and signature for third and subsequent joint inventors).

German Language Declaration

VERTRETUNGSVOLLMACHT: Als benannter Erfinder beauftrage ich hiermit den nachstehend benannten Patentanwalt (oder die nachstehend benannten Patentanwälte) und/oder Patent-Agenten mit der Verfolgung der vorliegenden Patentanmeldung sowie mit der Abwicklung aller damit verbundenen Geschäfte vor dem Patent- und Warenzeichenamt: *(Name und Registrationsnummer anführen)*

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. *(list name and registration number)*

And I hereby appoint

Customer No. 25227

Telefongespräche bitte richten an:
(Name und Telefonnummer)

Direct Telephone Calls to: *(name and telephone number)*

Ext. _____

Postanschrift:

Send Correspondence to:

Morrison and Foerster LLP
2000 Pennsylvania Ave., NW 20006-1888 Washington, DC
Telephone: (001) 202 887 1500 and Facsimile (001) 202 887 0763
or
Customer No. 25227

Voller Name des einzigen oder ursprünglichen Erfinders: Andreas Arndt	Full name of sole or first inventor: Andreas Arndt
Unterschrift des Erfinders Datum	Inventor's signature Date
Wohnsitz Algermissen, Deutschland	Residence Algermissen, Germany
Staatsangehörigkeit Deutsch	Citizenship German
Postanschrift Lindenallee 12 31191 Algermissen Deutschland	Post Office Addess Lindenallee 12 31191 Algermissen Germany
Voller Name des zweiten Miterfinders (falls zutreffend): Wolf Rüdiger Canders 2-D	Full name of second joint inventor, if any: Wolf Rüdiger Canders
Unterschrift des Erfinders Datum Wolf-Rüdiger Canders 21.09.01	Second Inventor's signature Date Wolf-Rüdiger Canders 21.09.01
Wohnsitz Osterode/Harz, Deutschland	Residence Osterode/Harz, Germany
Staatsangehörigkeit Deutsch	Citizenship German DEX
Postanschrift Fuchshaller Weg 38 37520 Osterode/Harz Deutschland	Post Office Address Fuchshaller Weg 38 37520 Osterode/Harz Germany

(Bitte entsprechende Informationen und Unterschriften im Falle von dritten und weiteren Miterfindern angeben).

(Supply similar information and signature for third and subsequent joint inventors).

Voller Name des dritten Miterfinders:	Full name of third joint inventor:
KARL MASCHER 3-04	KARL MASCHER
Unterschrift des Erfinders / Datum	Inventor's signature / Date
Karl Mascher 24.9.01	Karl Mascher 24.9.01
Wohnsitz	Residence
BERLIN, Deutschland	BERLIN, Germany
Staatsangehörigkeit	Citizenship
Deutsch	German DE
Postanschrift	Post Office Address
AM DACHSBAU 102 A	AM DACHSBAU 102 A
13503 BERLIN Deutschland	13503 BERLIN Germany

Voller Name des vierten Miterfinders:	Full name of fourth joint inventor:
Hardo May	Hardo May
Unterschrift des Erfinders / Datum	Inventor's signature / Date
Wohnsitz	Residence
Braunschweig, Deutschland	Braunschweig, Germany
Staatsangehörigkeit	Citizenship
Deutsch	German
Postanschrift	Post Office Address
Sportau Str. 14	Sportau Str. 14
38124 Braunschweig Deutschland	38124 Braunschweig Germany

Voller Name des fünften Miterfinders:	Full name of fifth joint inventor:
KLAUS SCHULER 4.04	KLAUS SCHULER
Unterschrift des Erfinders / Datum	Inventor's signature / Date
Klaus Schuler 20.09.01	Klaus Schuler 20.09.01
Wohnsitz	Residence
BERLIN, Deutschland	BERLIN, Germany
Staatsangehörigkeit	Citizenship
Deutsch	German DE
Postanschrift	Post Office Address
PFEFFERWEG 1	PFEFFERWEG 1
13589 BERLIN	13589 BERLIN

Voller Name des sechsten Miterfinders:	Full name of sixth joint inventor:
Prof. HERBERT WEH	Prof. HERBERT WEH
Unterschrift des Erfinders / Datum	Inventor's signature / Date
Wohnsitz	Residence
BRAUNSCHWEIG,	BRAUNSCHWEIG,
Staatsangehörigkeit	Citizenship
Deutsch	German
Postanschrift	Post Office Address
WOEHLERSTR. 20	WOEHLERSTR. 20
38116 BRAUNSCHWEIG	38116 BRAUNSCHWEIG

(Bitte entsprechende Informationen und Unterschriften im Falle von dritten und weiteren Miterfindern angeben).

(Supply similar information and signature for third and subsequent joint inventors).

Voller Name des achten Miterfinders (falls zutreffend):	Full name of eighth joint inventor, if any:
Holger Gerhard Wisken	Holger Gerhard Wisken
Unterschrift des Erfinders Datum: 26.09.01	Inventor's signature Date: 26.09.01
Wohnsitz: Wittingen,	Residence: Wittingen,
Staatsangehörigkeit: DE	Citizenship: DE
Postanschrift: Carl-~~Peteus~~ Peters-Str. 4, 29378 Wittingen	Post Office Address: Carl-~~Peteus~~ Peters-Str. 4, 29378 Wittingen
Voller Name des achten Miterfinders (falls zutreffend):	Full name of eighth joint inventor, if any:
Unterschrift des Erfinders Datum	Inventor's signature Date
Wohnsitz	Residence
Staatsangehörigkeit	Citizenship
Postanschrift	Post Office Address
Voller Name des neunten Miterfinders (falls zutreffend):	Full name of nineth joint inventor, if any:
Unterschrift des Erfinders Datum	Inventor's signature Date
Wohnsitz ,	Residence ,
Staatsangehörigkeit	Citizenship
Postanschrift	Post Office Address
Voller Name des zehnten Miterfinders (falls zutreffend):	Full name of tenth joint inventor, if any:
Unterschrift des Erfinders Datum	Inventor's signature Date
Wohnsitz ,	Residence ,
Staatsangehörigkeit	Citizenship
Postanschrift	Post Office Address

(Bitte entsprechende Informationen und Unterschriften im Falle von dritten und weiteren Miterfindern angeben).

(Supply similar information and signature for third and subsequent joint inventors).

Voller Name des dritten Miterfinders:	Full name of third joint inventor:
KARL MASCHER	KARL MASCHER
Unterschrift des Erfinders Datum	Inventor's signature Date
Wohnsitz	Residence
BERLIN, Deutschland	BERLIN, Germany
Staatsangehörigkeit	Citizenship
Deutsch	German
Postanschrift	Post Office Address
AM DACHSBAU 102 A	AM DACHSBAU 102 A
13503 BERLIN Deutschland	13503 BERLIN Germany
Voller Name des vierten Miterfinders:	Full name of fourth joint inventor:
Hardo May	Hardo May
Unterschrift des Erfinders Datum	Inventor's signature Date
Hardo May 25.09.01	Hardo May 25.09.01
Wohnsitz	Residence
Braunschweig, Deutschland	Braunschweig, Germany
Staatsangehörigkeit	Citizenship
Deutsch	German DE
Postanschrift	Post Office Address
~~Sportau Str. 14~~ Sprottau Str. 14	~~Sportau Str. 14~~ Sprottau Str. 14
38124 Braunschweig Deutschland	38124 Braunschweig Germany
Voller Name des fünften Miterfinders:	Full name of fifth joint inventor:
KLAUS SCHULER	KLAUS SCHULER
Unterschrift des Erfinders Datum	Inventor's signature Date
Wohnsitz	Residence
BERLIN, Deutschland	BERLIN, Germany
Staatsangehörigkeit	Citizenship
Deutsch	German
Postanschrift	Post Office Address
PFEFFERWEG 1	PFEFFERWEG 1
13589 BERLIN	13589 BERLIN
Voller Name des sechsten Miterfinders:	Full name of sixth joint inventor:
Prof. HERBERT WEH	Prof. HERBERT WEH
Unterschrift des Erfinders Datum	Inventor's signature Date
Wohnsitz	Residence
BRAUNSCHWEIG,	BRAUNSCHWEIG,
Staatsangehörigkeit	Citizenship
Deutsch	German
Postanschrift	Post Office Address
WOEHLERSTR. 20	WOEHLERSTR. 20
38116 BRAUNSCHWEIG	38116 BRAUNSCHWEIG

(Bitte entsprechende Informationen und Unterschriften im Falle von dritten und weiteren Miterfindern angeben).

(Supply similar information and signature for third and subsequent joint inventors).

Voller Name des dritten Miterfinders:	Full name of third joint inventor:
KARL MASCHER	KARL MASCHER
Unterschrift des Erfinders Datum	Inventor's signature Date
Wohnsitz	Residence
BERLIN, Deutschland	BERLIN, Germany
Staatsangehörigkeit	Citizenship
Deutsch	German
Postanschrift	Post Office Address
AM DACHSBAU 102 A	AM DACHSBAU 102 A
13503 BERLIN Deutschland	13503 BERLIN Germany

Voller Name des vierten Miterfinders:	Full name of fourth joint inventor:
Hardo May	Hardo May
Unterschrift des Erfinders Datum	Inventor's signature Date
Wohnsitz	Residence
Braunschweig, Deutschland	Braunschweig, Germany
Staatsangehörigkeit	Citizenship
Deutsch	German
Postanschrift	Post Office Address
Sportau Str. 14	Sportau Str. 14
38124 Braunschweig Deutschland	38124 Braunschweig Germany

Voller Name des fünften Miterfinders:	Full name of fifth joint inventor:
KLAUS SCHULER	KLAUS SCHULER
Unterschrift des Erfinders Datum	Inventor's signature Date
Wohnsitz	Residence
BERLIN, Deutschland	BERLIN, Germany
Staatsangehörigkeit	Citizenship
Deutsch	German
Postanschrift	Post Office Address
PFEFFERWEG 1	PFEFFERWEG 1
13589 BERLIN	13589 BERLIN

Voller Name des sechsten Miterfinders:	Full name of sixth joint inventor:
Prof. HERBERT WEH	Prof. HERBERT WEH
Unterschrift des Erfinders Datum	Inventor's signature Date
H. Weh 1.10.01	H. Weh 10.01.01
Wohnsitz	Residence
BRAUNSCHWEIG,	BRAUNSCHWEIG,
Staatsangehörigkeit	Citizenship
Deutsch	German DEX
Postanschrift	Post Office Address
WOEHLERSTR. 20	WOEHLERSTR. 20
38116 BRAUNSCHWEIG	38116 BRAUNSCHWEIG

(Bitte entsprechende Informationen und Unterschriften im Falle von dritten und weiteren Miterfindern angeben).

(Supply similar information and signature for third and subsequent joint inventors).